

SERVICE SHEET No. 510

*Revised June, 1959
Reprinted March, 1965*

Models D1, D3, D5 and D7

USEFUL DATA

PETROL TANK CAPACITY (approx.)				1¾ galls. (8 litres). D5 and D7 2 galls.																
“PETROIL” MIXTURE		2 filler cap measures per gallon petrol with 6¼ in. filler. 2½ filler cap measures per gallon petrol with 5 in. filler.																
GEARBOX CAPACITY		¾ pint (425 c.c.).																
BORE	D1—52 mm. D3—57 mm. D5 and D7—61.5 mm.																
STROKE	58 mm.																
CAPACITY (Swept Volume)	D1—123 c.c. D3—148 c.c. D5 and D7—174 c.c.																
PISTON RING GAP		Maximum .013 in. (.325 mm.). Minimum .009 in. (.225 mm.).																
IGNITION TIMING		Piston distance before top dead centre with points just opening, 1/32 in. (3.75 mm.), D1 and D3 1/16 in. (1.587 mm.) D5 and D7.																
PLUG POINT GAP015 in. to .018 in. (.38 to .45 mm.).																
GEAR RATIOS	<table border="0" style="margin-left: 40px;"> <thead> <tr> <th></th> <th>Standard</th> <th>Competition</th> <th>D5 and D7</th> </tr> </thead> <tbody> <tr> <td>Top</td> <td>7.0 to 1</td> <td>8.64 to 1</td> <td>6.48 to 1</td> </tr> <tr> <td>Second</td> <td>11.7 to 1</td> <td>14.45 to 1</td> <td>10.74 to 1</td> </tr> <tr> <td>First</td> <td>22.0 to 1</td> <td>27.1 to 1</td> <td>20.2 to 1</td> </tr> </tbody> </table>		Standard	Competition	D5 and D7	Top	7.0 to 1	8.64 to 1	6.48 to 1	Second	11.7 to 1	14.45 to 1	10.74 to 1	First	22.0 to 1	27.1 to 1	20.2 to 1
	Standard	Competition	D5 and D7																	
Top	7.0 to 1	8.64 to 1	6.48 to 1																	
Second	11.7 to 1	14.45 to 1	10.74 to 1																	
First	22.0 to 1	27.1 to 1	20.2 to 1																	
TYRE SIZE,	Front	2.75 × 19. D5 and D7, 3.00 × 18.																
	Rear	Standard 2.75 × 19; Competition 3.25 × 19; D5 and D7, 3.00 × 18.																
TYRE PRESSURES	Front	16 lbs. sq. in. (1.125 kg. per sq. cm.). D5 and D7, 16 lbs. per square inch.																
(Standard Model)	Rear	20-22 lbs. sq. in. (1.55 kg. per sq. cm.). D5 and D7, 24 lbs. per square inch.																
FRONT CHAIN (3.75 in. × .225 in.)				50 links.																
REAR CHAIN (½ in. × .205 in.)																				
Standard,	Rigid Frame	...		116 links.																
	Spring Frame	...		117 links (D3, D5 121 links, D7 Swinging Arm 120 links).																
Competition	Rigid Frame	...		122 links.																
	Spring Frame	...		123 links.																
STANDARD CARBURETTOR JET				D1—75 D3—90, D5 and D7—140.																
JET NEEDLE POSITION		Second notch from top, D5 and D7, fourth.																

B.S.A. MOTOR CYCLES LTD., Service Department, Armoury Road, Birmingham 11.

B.S.A. PRESS